


# Końcówki kablowe

## Końcówki rurkowe seria standard

- Z rurki
- Materiał: Miedź elektrolityczna 99,9 % E-CU DIN 40500
- Powierzchnia: cynowane



Cu

dostępna z lub bez otworu, na przykład 29 09 00/S (podać w zamówieniu xx xx xx/s)


29 09 00

29 09 00/S

Art. nr.	p. prz.	M	Zaciskanie		d1	d2	d4	a	b	c1	c2	l	ciężar/100 sztuk	sztuk	kasetka
			wąskie	szersze											
29 09 00	0,75	3	1		1,3	3,2	2,8	6	6,0	3,25	4,0	12	0,060	100	2000
29 09 02		4	1			4,3			6,5	4,00	5,0	13	0,060	100	2000
29 09 04	1,5	3	1		1,8	3,2	3,3	6	6,5	3,25	4,0	12	0,080	100	2000
29 09 06		4	1			4,3			6,5	4,00	5,0	13	0,080	100	2000
29 09 08		5	1			5,3			7,5	4,75	5,5	14	0,080	100	2000
29 09 10		6	1			6,5			9,0	6,50	6,5	16	0,090	100	2000
29 09 12	2,5	3	1		2,3	3,2	4,2	6	7,5	3,25	4,0	12	0,120	100	2000
29 09 14		4	1			4,3			7,5	4,00	5,0	13	0,120	100	2000
29 09 16		5	1			5,3			8,5	4,75	5,5	14	0,130	100	2000
29 09 18		6	1			6,5			9,5	6,50	6,5	16	0,150	100	2000
29 09 20		8	1			8,5			13,0	7,75	9,5	20	0,180	100	2000
29 09 22	4	4	1		3	4,3	5	8	8,5	4,75	5,5	17	0,210	100	2000
29 09 24		5	1			5,3			9,0	4,75	6,0	17	0,210	100	2000
29 09 26		6	1			6,5			10,0	6,50	6,5	19	0,220	100	2000
29 09 28		8	1			8,5			13,0	8,50	9,5	22	0,280	100	2000
29 09 30	6	4	1		3,5	4,3	6,5	9	8,5	5,00	5,5	18	0,290	100	1800
29 09 32		5	1			5,3			10,0	6,50	7,5	21	0,470	100	1800
29 09 34		6	1			6,5			12,0	6,50	7,5	21	0,470	100	1400
29 09 36		8	1			8,5			15,0	10,00	10,0	23	0,540	100	1400
29 09 38	10	5	1		4,5	5,3	7	10	12,0	6,50	7,5	22	0,500	100	1000
29 09 40		6	1			6,5			12,0	6,50	7,5	22	0,490	100	1000
29 09 42		8	1			8,5			15,0	10,00	10,0	25	0,580	100	800
29 09 44		10	1			10,5			17,0	12,00	12,0	27	0,620	100	600
29 09 46		12	1			13,0			19,0	13,00	13,0	29	0,640	100	600
29 09 48	16	5	1	1	5,5	5,3	8,5	13	12,0	5,50	6,5	26	0,840	100	600
29 09 50		6	1	1		6,5			12,0	6,25	7,5	27	0,860	100	600
29 09 52		8	1	1		8,5			15,0	8,50	9,5	29	0,930	100	400
29 09 54		10	1	1		10,5			17,0	10,50	11,5	31	0,990	100	400
29 09 56		12	1	1		13,0			19,0	12,00	13,0	33	1,020	100	400
29 09 58	25	6	2	1	7	6,5	10	15	14,0	7,50	7,5	30	1,200	50	400
29 09 60		8	2	1		8,5			16,0	10,00	10,0	32	1,300	50	400
29 09 62		10	2	1		10,5			18,0	12,00	12,0	34	1,550	50	300
29 09 64		12	2	1		13,0			19,0	13,00	13,0	35	1,400	50	300
29 09 66	35	6	2	1	8,5	6,5	12	17	17,0	7,50	7,5	32	1,850	40	240
29 09 68		8	2	1		8,5			17,0	10,00	10,0	34	2,000	40	240
29 09 70		10	2	1		10,5			19,0	12,00	12,0	37	2,150	40	160
29 09 72		12	2	1		13,0			21,0	13,00	13,0	38	2,120	40	160
29 09 74		16	2	1		17,0			26,0	16,00	16,0	42	2,240	35	140
29 09 76	50	6	2	1	10	6,5	14	19	20,0	10,00	10,0	37	3,000	25	150
29 09 78		8	2	1		8,5			20,0	10,00	10,0	37	3,000	25	150
29 09 80		10	2	1		10,5			20,0	12,00	12,0	39	3,080	25	150
29 09 82		12	2	1		13,0			23,0	13,00	13,0	43	3,230	25	100
29 09 84		16	2	1		17,0			28,0	16,00	16,0	46	3,400	25	100
29 09 85	70	6	2	1	12	6,5	16,5	21	23,0	10,00	10,0	43	4,500	25	100
29 09 86		8	2	1		8,5			23,0	10,00	10,0	43	4,400	25	100
29 09 88		10	2	1		10,5			23,0	12,00	12,0	44	4,500	25	100
29 09 90		12	2	1		13,0			23,0	13,00	13,0	46	4,600	25	100
29 09 91		14	2	1		15,0			23,0	14,50	14,5	48	4,770	25	100
29 09 92		16	2	1		17,0			28,0	16,00	16,0	50	4,300	25	100
29 09 94	95	8	2	1	13,5	8,5	18	25	26,0	12,00	12,0	48	5,450	25	100
29 09 96		10	2	1		10,5			26,0	12,00	12,0	48	5,450	25	100
29 09 98		12	2	1		13,0			26,0	13,00	13,0	49	5,550	25	100
29 09 99		14	2	1		15,0			26,0	14,50	14,5	51	5,600	10	40
29 10 00		16	2	1		17,0			28,0	16,00	16,0	54	5,800	10	40
29 10 02		20	2	1		21,0			36,0	22,00	22,0	60	6,700	10	40

## Końcówki rurkowe seria standard (ciąg dalszy)

- Z rurki
- Materiał: Miedź elektrolityczna 99,9 % E-CU DIN 40500
- Powierzchnia: cynowane



Cu

Dostępne z lub bez otworu, na przykład 29 09 04/S (podać w zamówieniu xx xx xx/s)

29 09 04

29 09 04/S

Art. nr.	p. prz.	M	Zaciskanie										ciężar/100 sztuk	sztuk	kasetka
			wąskie	szerokie	d1	d2	d4	a	b	c1	c2	l			
29 00 04	120	8	2	1	15	8,5	19,5	26	28,0	14,00	14,0	51	6,700	20	20
29 00 06		10	2	1		10,5			28,0	14,00	14,0	51	6,550	20	80
29 00 08		12	2	1		13,0			28,0	14,00	14,0	51	6,400	20	80
29 00 09		14	2	1		15,0			28,0	15,00	15,0	52	6,450	18	72
29 00 10		16	2	1		17,0			30,0	16,00	16,0	54	6,500	18	72
29 00 12		20	2	1		21,0			36,0	22,00	22,0	63	7,700	15	60
29 00 14	150	10	2	1	16,5	10,5	21	30	31,0	14,00	14,0	56	7,600	12	72
29 00 16		12	2	1		13,0			31,0	15,00	15,0	57	7,700	12	72
29 00 17		14	2	1		15,0			31,0	15,00	15,0	57	7,650	12	72
29 00 18		16	2	1		17,0			31,0	16,00	16,0	58	7,500	12	48
29 00 20		20	2	1		21,0			36,0	22,00	22,0	66	8,800	12	48
29 00 22	185	12	2	1	19	13,0	24	30	35,0	18,00	18,0	65	11,800	20	40
29 00 23		14	2	1		15,0			35,0	18,00	18,0	65	11,400	20	40
29 00 24		16	2	1		17,0			35,0	18,00	18,0	65	11,250	20	40
29 00 26		20	2	1		21,0			39,0	22,00	22,0	69	12,000	20	40
29 00 28	240	12	4	2	21	13,0	26	35	39,0	21,50	19,0	72	14,550	15	30
29 00 29		14	4	2		15,0			39,0	21,50	19,0	72	14,250	15	30
29 00 30		16	4	2		17,0			39,0	21,50	19,0	72	14,100	15	30
29 00 34	300	12	4	2	23,5	13,0	29,5	44	43,0	24,00	24,0	72	23,350	8	16
29 00 36		14	4	2		15,0			43,0	24,00	24,0	87	23,150	8	16
29 00 38		16	4	2		17,0			43,0	24,00	24,0	87	22,750	8	16
29 00 40		20	4	2		21,0			43,0	24,00	24,0	87	22,200	8	16
29 00 46	400	16	4	2	27	17,0	34	44	49,0	24,00	24,0	90	32,000	5	10
29 00 48		20	4	2		21,0			49,0	24,00	24,0	90	31,400	5	10
29 00 41	500	16	4	2	31	17,0		70	55,0				47,860	4	8
29 00 43		20	4	2		21,0			55,0				47,800	4	8
29 00 45	625	16	4	2	34	17,0		70	60,0				51,350	3	6
29 00 47		20	4	2		21,0			60,0				50,600	3	6

haupa®

...rozwiązania, które przekonują